
## **Technical Specification**

## Double cab pick-up 4WD-1 (One) unit

S.N.	CRITERIA	Requirements	OFFERED SPECIFICATION
1	General	Right Hand Drive Model with four wheel Drive, Double cab pick-up diesel engine Type Vehicle suitable for operation under rough and hilly road and adverse climatic condition at operating altitude of 2500 meters and in ambient temperature varying between -5 to 50 degree Celsius. Gross Vehicle Weight (GVW) of the vehicle shall not less than 2,700 kg and shall have seating capacity for at least 5 Persons including driver.	Make: Model: Year of Mfg.: Country of Origin:
2	Engine	Four strokes four cylinders, water cooled diesel Engine not less than 2100 cc developing maximum rated power output not less than 110 HP at governed RPM with Torque Should not be less than 260 NM @ govern RPM. Engine fully equipped with accessories for efficient full load operation of the Vehicle at operating conditions, cold starting device, direct electric starting system, heavy duty fuel filter.	Make: Model:
3	Emission Standard	The Emission Standard of the vehicle should be capable of meeting applicable Nepal Vehicle Mass emission standard, which is to be certified by Department of Transport Management, Nepal	
4	Gauges	Speedometer, Water Temperature, Fuel, Oil Pressure etc as necessary for the efficient operation and maintenance, signal for 4 WD.	
5	Clutch	Single plate, Dry friction.	
6	Transmission	Floor mounted Manual shift at least five forward and one reverse, all forward synchromesh	
-7	Tyre size	Standard, Radial, Tubeless	
8	Suspension & Brakes	Leaf Spring / Coil Spring / Torsion bar Shock Absorbers at front and rear. Brake: - Front Ventilated Disc type, Rear - Disc/Drum Type.	
9	Steering	Power steering	
10	Turning radius	Turning Radius Not more than 7 Meters.	
11	Ground Clearance	High ground clearance will be preferred, at full load ground clearance shall not be less than 200 mm.	
12	Cab	4 side metallic door and all metallic cab with insulated roof, laminated/tinted glass wind screen washers and wiper, comfortable and adjustable seats for driver and co-passenger, front and middle seat will be front facing, two sun visor, rear view mirror, two side view mirror and metallic rear body with lockable cargo box.	
13	Fuel Tank Capacity	Minimum 55 Ltrs.	
14	Chassis and frame	Steel, heavy duty suitable for rough road conditions with tow hook in front and rear.	







15	Essential	The vehicle should be equipped with:	
	Accessories	Head light tail and rear light, reversing light and turn signal	
		Cabin light	
		Odometer	
		1 spare wheel with tyre and tube	
		Jack and Handle	
		Seat belts for drive and co-driver	
		Air conditioner with heater	
		Power windows (front & rear)	
		Audio System with CD/MP3 Player	
		Air Bag with ABS	
		Floor carpet,	
		: To be equipped with all accessories offered in standard	
		model but not limited to the above items.	
16	Instruction	All signs and instruction in the vehicle shall be in English.	
97	Proven	1. The Vehicle offered shall be a current model under standard production	
	Performance	by the manufacture for at least one year.	
	124	2. The bidder shall provide the manufacture's data of the performance of the unit to include the fuel consumption, performance curve of the Engine	
		and production capacity of the unit.	
18	Manuals	One copy of the operators and owner's instruction manual in English.	
19	Tools	A set of tools for general maintenance shall be supplied.	
	Color	Standard	
20	Warranty	Manufacturer shall provide a minimum one year warranty after acceptance.	
21	Delivery	The Double cab Pick-up One unit shall be delivered to the	
		Lumbini Provenance, Ministry of Agriculture, Food	
		Technology and Land management, Mukam Butwal Rupandehi	



Name: Laxman Acharya

Designation: Mechanical Engineer

Office: DoR, HED, Butwal

Mechanical Engineer,



